

AMENDMENTS TO THE CLAIMS

1. **(Currently Amended)** A method for generating a wide image video sequence using a device having at least two video cameras substantially co-located in a predetermined relationship to each other such that there will be an overlap between images from the respective cameras, said method comprising the steps of:

a. forming a synthetic image from images of the respective cameras by (i) identifying corresponding parts in overlapping parts of the images, (ii) determining the relation between the respective coordinates for the pixels in the individual cameras and in the synthetic image, and (iii) calculating calibration parameters from said relation, said calculated calibration parameters being unique for the at least two cameras and their current location as related to the object being recorded;

b. synchronously recording video sequences using each of said at least two video cameras; and

c. generating a wide image video sequence by combining said synchronously recorded video sequences using said calculated calibration parameters,

wherein the step of calculating calibration parameters comprises the step of calculating a projective transform by comparing spatial characteristics of said corresponding parts with each other, and wherein the step of generating the wide image video sequence is performed using said projective transform.

2. **(Previously Presented)** A method according to claim 1, wherein the synchronously recorded video sequences are stored in a memory storage area.

3. **(Previously Presented)** A method according to claim 1, wherein the synchronously recorded video sequences are used concurrently for generating the wide image video sequence.

4. **(Previously Presented)** A method according to claim 3, wherein the wide image video sequence is transmitted live.

5. **(Previously Presented)** A method according to claim 3, wherein the wide image video sequence is stored on a memory storage area.

6. **(Previously Presented)** A method according to claim 1, wherein calculating the calibration comprises the following steps:

- a. starting a calibration process;
- b. synchronizing the sequences from each of the at least two cameras;
- c. computing inter-image projective transformations;
- d. using the transformations to refer each image to a common reference frame;
- e. selecting a real or virtual reference camera such that certain lines on the pitch or stadium are substantially horizontal and substantially parallel in the wide image;
- f. selecting a rectangular region of interest within the wide image; and
- g. storing the computed values resulting from the calibration process to be used as the calibration parameters.

7. **(Previously Presented)** A method according to claim 6 further comprising the step of determining lens distortion parameters for each camera, and correcting radial distortion in each image.

8. **(Previously Presented)** A method according to claim 6 further comprising the step of selecting non-linear distortion parameters to reduce perspective distortion of the wide image.

9. **(Canceled)**

10. **(Previously Presented)** A method according to claim 1 in which step b is performed automatically by an algorithm for identification of corresponding features in

concurrent video images and the coordinates for the corresponding features are input via a computer means.

11. **(Previously Presented)** A method according to claim 1 further comprising performing the following steps until completing the generation of the wide image video sequence:

- a. applying the calculated calibration parameters;
 - b. until the end of the sequence is reached, for each pixel in the wide image, computing and storing parameters describing (1) which pixels from which images contribute to the respective pixels in the wide image and (2) how much each of the respective pixels contributes to the wide image;
 - c. retrieving one new image from each camera;
 - d. selectively updating the parameters needed to transform intensities in one or more of the cameras to eliminate visible seams;
 - e. selectively adjusting intensities in the images from one or more of the cameras;
- and
- f. creating the current seamless, wide image from the current images from each camera;
 - g. outputting the wide image to a display or to a memory storage area.

12. **(Previously Presented)** A method according to claim 11, wherein the new images from each camera are read from live sources, each such source comprising a video camera.

13. **(Previously Presented)** A method according to claim 11 wherein the new images from each video camera are read from a memory storage area.

14. **(Currently Amended)** A device having at least two video cameras substantially co-located and arranged in a predetermined relationship to each other such that there will be an overlap between images from the respective cameras, a processor, at least one memory storage area, wherein the processor is configured to:

a. form a synthetic image from images of the respective cameras by (i) identifying corresponding parts in overlapping parts of the images, (ii) determining the relation between the respective coordinates for the pixels in the individual cameras and in the synthetic image, and (iii) calculating calibration parameters from said relation **by calculating a projective transform by comparing spatial characteristics of said corresponding parts with each other**, said calculated calibration parameters being unique for the at least two cameras and their current location as related to the object being recorded;

b. synchronously record video sequences using each of said at least two video cameras; and

c. generate a wide image video sequence by combining said synchronously recorded video sequences using said calculated calibration parameters **and using said projective transform**.

15. **(Previously Presented)** The device of claim 14, wherein the synchronously recorded video sequences are stored in a memory storage area.

16. **(Previously Presented)** The device of claim 14, wherein the synchronously recorded video sequences are used concurrently for generating the wide image video sequence.

17. **(Previously Presented)** The device of claim 14, wherein to calculate calibration parameters, the processor is further configured to:

- a. start a calibration process;
- b. synchronize the sequences from each of the at least two cameras;
- c. compute inter-image projective transformations;
- d. use the transformations to refer each image to a common reference frame;
- e. select a real or virtual reference camera such that certain lines on the pitch or stadium are substantially horizontal and substantially parallel in the wide image;
- f. select a rectangular region of interest within the wide image; and
- g. store the computed values resulting from the calibration process to be used as the calibration parameters.

18. **(Previously Presented)** The device of claim 14, wherein to calculate the calibration parameters, the processor is further configured to determine lens distortion parameters for each camera, and correct radial distortion in each image produced.

19. **(Previously Presented)** The device of claim 14, wherein to calculate the calibration parameters, the processor is further configured to select non-linear distortion parameters to reduce perspective distortion of the wide image.

20. **(Canceled)**

21. **(Previously Presented)** The device of claim 14, wherein step b is performed automatically by an algorithm for identification of corresponding features in concurrent video images and the coordinates for these corresponding features are input to a computer storage area.

22. **(Previously Presented)** The device of claim 14, wherein the processor is further configured to:

- a. apply the calculated calibration parameters;
- b. until the end of the sequence is reached, for each pixel in the wide image, compute and store parameters describing (1) which pixels from which images contribute to the respective pixels in the wide image and (2) how much each of the respective pixels contributes to the wide image;
- c. retrieve one new image from each camera;
- d. selectively update the parameters needed to transform intensities in one or more of the cameras to eliminate visible seams;
- e. selectively adjust intensities in the images from one or more of the cameras; and
- f. create the current seamless, wide image from the current images from each camera;
- g. output the wide image to a display or to a memory storage area.

23. **(Previously Presented)** The device of claim 22, wherein the new images from each camera are read from live sources, each such source comprising a video camera.

24. **(Previously Presented)** The device of claim 22, wherein the new images from each video camera are read from a memory storage area.

25. **(Currently Amended)** A computer-readable medium having computer-readable program code portions stored therein, the computer-readable program code portions comprising executable portions that cause a device having at least two video cameras substantially co-located in a predetermined relationship to each other such that there will be an overlap between images from the respective cameras to:

a. form a synthetic image from images of the respective cameras by (i) identifying corresponding parts in overlapping parts of the images, (ii) determining the relation between the respective coordinates for the pixels in the individual cameras and in the synthetic image, and (iii) calculating calibration parameters from said relation by calculating a projective transform by comparing spatial characteristics of said corresponding parts with each other, said calculated calibration parameters being unique for the at least two cameras and their current location as related to the object being recorded;

b. synchronously record video sequences using each of said at least two video cameras; and

c. generate a wide image video sequence by combining said synchronously recorded video sequences using said calculated calibration parameters and using said projective transform.

26. **(Previously Presented)** The computer-readable medium of claim 25, wherein the synchronously recorded video sequences are stored in a memory storage area.

27. **(Previously Presented)** The computer-readable medium of claim 25, wherein the synchronously recorded video sequences are used concurrently for generating the wide image video sequence.

28. **(Previously Presented)** The computer-readable medium of claim 25, wherein to calculate the calibration parameters, the computer-readable medium further comprises executable portions that cause the device to:

- a. start a calibration process;
- b. synchronize the sequences from each of the at least two cameras;
- c. compute inter-image projective transformations;
- d. use the transformations to refer each image to a common reference frame;
- e. select a real or virtual reference camera such that certain lines on the pitch or stadium are substantially horizontal and substantially parallel in the wide image;
- f. select a rectangular region of interest within the wide image; and
- g. store the computed values resulting from the calibration process to be used as the calibration parameters.

29. **(Previously Presented)** The computer-readable medium of claim 28, further comprising executable portions that cause the device to determine lens distortion parameters for each camera, and correct radial distortion in each image produced.

30. **(Previously Presented)** The computer-readable medium of claim 28, further comprising executable portions that cause the device to select non-linear distortion parameters to reduce perspective distortion of the wide image.

31. **(Canceled)**

32. **(Previously Presented)** The computer-readable medium of claim 28, wherein step b is performed automatically by an algorithm for identification of corresponding features in concurrent video images and the coordinates for the corresponding features are input to a computer means.

33. **(Previously Presented)** The computer-readable medium of claim 28, further comprising executable portions that cause the device to:

- a. apply the calculated calibration parameters;
- b. until the end of the sequence is reached, for each pixel in the wide image, compute and store parameters describing (1) which pixels from which images contribute to the respective pixels in the wide image and (2) how much each of the respective pixels contributes to the wide image;
- c. retrieve one new image from each camera;
- d. selectively update the parameters needed to transform intensities in one or more of the cameras to eliminate visible seams;
- e. selectively adjust intensities in the images from one or more of the cameras; and
- f. create the current seamless, wide image from the current images from each camera;
- g. output the wide image to a display or to a memory storage area.

34. **(Previously Presented)** The computer-readable medium of claim 28, wherein the new images from each camera are read from live sources, each such source comprising a video camera.

35. **(Previously Presented)** The computer-readable medium of claim 28, wherein the new images from each video camera are read from a memory storage area.

36. **(Currently Amended)** A video recording apparatus having at least two video cameras substantially co-located in a predetermined relationship to each other such that there will be an overlap between images from the respective cameras, the video recording apparatus comprising:

- a microprocessor (130);
- a memory storage area (120) storing a program for:
 - a. forming a synthetic image from images of the respective cameras by (i) identifying corresponding parts in overlapping parts of the images, (ii) determining the relation

between the respective coordinates for the pixels in the individual cameras and in the synthetic image, and (iii) calculating calibration parameters from said relation **by calculating a projective transform by comparing spatial characteristics of said corresponding parts with each other**, said calculated calibration parameters being unique for the at least two cameras and their current location as related to the object being recorded,

b. synchronously recording video sequences using each of said at least two video cameras, and

c. generating a wide image video sequence by combining said synchronously recorded video sequences using said calculated calibration parameters **and using said projective transform**,

 a read and write memory storage area (140) for storing data relating to recorded video sequences from the at least two video cameras;

 an input component (300) for receiving input of parameters, and input of recorded video sequences; and

 an output component (300) for outputting of a wide image video sequence.